

TND4004

High-Resolution DSP Color Dome Camera



Full-featured high-resolution fixed dome camera delivers crisp, crystal clear color images even in low light.


- ●480TVL horizontal resolution
- Versatile power requirements 24VAC/12VDC
- Line lock with phase adjustment/Internal sync.
- ●High performance built-in 2.8~6mm vari-focal full auto-iris lens
- ●Camera rotates 180°, lens tilts 50° with lock screws for secure positioning of camera
- •Four unique white balance modes including full automatic
- Back light compensation
- Built-in isolation circuitry
- Off white with black cover
- ■Low profile 4.5" diameter



$\textbf{High-Resolution DSP Color Dome Camera } \textcolor{red}{\textbf{TND4004}}$

PROFILE





SPECIFICATIONS

Pick-up Device	1/3" Color interline transfer CCD
Effective Picture Element	768 (H) ×494 (V)
Scanning Area	4.88mm (H) ×3.66mm (V)
TV System	NTSC compatible
Scanning System	2:1 interlaced
Scanning Frequency	LL:15.75kHz (H), 60Hz (V)
	INT:15.734kHz (H), 59.95Hz (V)
Synchronization	Line-lock/Internal
Resolution	480TV lines (H), 350TV lines (V)
S/N Ratio	50dB
Minimum Illumination	3lx (F1.4)
Automatic Gain Control(AGC)	Built-in
Sensitivity Up Control	With ON-OFF switch
White Balance	ATW/AWC/Manual/Preset
Backlight Compensation	With ON-OFF switch
Video Out	VBS 1.0Vp-p 75Ω, Terminal strip
Built-in Lens	F1.4, f=2.8~6mm Var-focal, Auto-iris
Angle of View	Horizontal : 47° (Tele) ~96° (Wide)
	Vertical : 36° (Tele) ~72° (Wide)
Power Source	AC24V / DC12V
Power Consumption	Approx. 3.5W
Ambient Temperature	-10°~ +50°C (14°~ 122°F)
Ambient Humidity	Less than 90%
Dimensions	Diameter : 116mm (4-9/16")
	Height: 106mm (4-3/16")
Weight	500g (1.1lbs)

NOTE: Design and specifications are subject to change without prior notice
Dimensions and weight are approximate.

OPTIONAL ACCESSORIES







ELMO CO., LTD.

6-14, Meizen-cho, Mizuho-ku, Nagoya, 467-8567 Japan E-mail:foreign-div@elmo.co.jp

ELMO (Europe) G.m.b.H. Neanderstr 18, 40233 Düsseldorf, Germany

Tel. 0211-376051-53 Fax.0211-376630

E-mail:elmoeurope@AOL.com Web:http://www.elmo.de/

Additional technical information is available from any of the following subsidiary companies

ELMO Mfg. Corp. 1478 Old Country Road, Plainview, NY 11803-5034, U.S.A. Tel. 516-501-1400 Fax. 516-501-0429 E-mail:elmo@elmousa.com
Web:http://www.elmousa.com

ELMO Canada Mfg. Corp.

44 West Drive, Brampton, Ontario, L6T 3T6, Canada Tel. 905-453-7880 Fax.905-453-2391 F-mail:info@elmocanada.com Web:http://www.elmocanada.com

Distributed by